

# sDAS Dual Band HEU

## HEU-2/4\_01

### Overview

sDAS series is a fiber Distribution Antenna System. The sDAS offers the industry leading and most innovative technology to help mobile operator extend the RF signal coverage into any indoor/outdoor environment from small to large scale. Indoor /outdoor coverage network becomes a manageable services and a new business model.



The sDAS system includes the HEU and RAU. The HEU can take RF signal from any source like Macro/Pico/Repeater/Small Cell and distribute the signal to RAUs in different locations via the single fiber. Each HEU can convert and distribute the RF signal to max. six RAUs to 5km distance. Both star and daisy chain topology are supported

### Key Features

- Distribute the LTE signal via a fiber network
- Source/Technology independent
- Star & Daisy chain hybrid topology
- Optics/RF Auto-calibration
- Multi-operator
- SNMP
- RoHS compliant

### Applications

- Indoor coverage
- Tunnel coverage
- Rural area signal extension
- Shadow area signal enhancement

#### TranSystem. Inc.

Tel: + 886-3-578-0393 Fax: + 886-3-578-4111  
Inquiries: sales@transystem.com.tw

Address: No. 1-2, Li-Hsin Rd I, Science-Based Industrial Park,  
Hsinchu, Taiwan, R.O.C.  
Web site: <http://www.transystem.com.tw>





## Specification

HEU-2/4_01		
RF Interface	RF Interface	N Type Female x 2
	RF1	Uplink : 1850 ~ 1910MHz
		Downlink : 1930 ~ 1990MHz
	RF2	Uplink : 1710 ~ 1755MHz
		Downlink : 2110 ~ 2155MHz
	Input Power Range	+10 ~ +30 dBm per port
	Power Overload Protection	Shut down downlink path when RF input power > +35dBm per port
Input Return Loss	≥14dB	
Fiber Interface	Fiber Connector	SC/APC x 2, each fiber interface supports up to 3ea RAUs in daisy chain configuration
	Wavelength	Downlink : 1550nm Uplink : 1310nm
	Laser O/P Power	5.5dBm typical. 4dBm minimum
	Optical RX Sensitivity	-8.5dBm
Power, Control and Monitoring	Interface	10/100 BaseT, RJ45 connector
	Power Input	802.3at
	DC Input Range	+36 ~ +58 VDC
	Power Consumption	12W
Environmental	Operating Temp Range	0 ~ +45 °C
Dimensions & Weight	Dimensions	218 (L) x 146(W) x 42(H) mm
	Weight	1.4 Kg
Mounting		Standard 1U rack mount interface
<b>HEU LED</b>	<b>Color</b>	<b>Description</b>
Power	Green	Power on
	Red	HEU system DC abnormal
HEU	Green	Normal mode
	Flash Green	1. Calibration mode, or 2. Environment sensing mode, or 3. Firmware upgrade
	Red	Failure alarm
RF1/RF2	Green	RF signal detected
	Dark	No RF signal
RAU1/2/3	Green	RAU has been provisioned and calibrated
	Flash Green	RAU has been provisioned but is standby for calibration or under diagnostic test or firmware upgrade
	Red	RAU connection failed after provisioned
	Dark	RAU doesn't provision yet

\* Specifications are subject to change without prior notice

### TranSystem. Inc.

Tel: + 886-3-578-0393 Fax: + 886-3-578-4111  
Inquiries: sales@transystem.com.tw

Address: No. 1-2, Li-Hsin Rd I, Science-Based Industrial Park,  
Hsinchu, Taiwan, R.O.C.  
Web site: <http://www.transystem.com.tw>

