

# TAM-A21

## 21dB MMDS Mesh Antenna

### Key Feature

- Can be used with AiDC<sup>+</sup>, LiDC, PLC-100 and PLC200.

### Specifications

Category	Description
Frequency Range	2100 ~ 2700 MHz
Gain	21 dB ± 1 dB
3 dB Beamwidth	13.0° ± 1.5°
Side Lobe Level	-17 dB ± 3 dB
Front to Back Ratio	> 26 dB
Over Back Hemisphere	18 dB Min
At 180 Degree	25 dB Min
Polarization	V / H
Reflector Material	Steel
Reflector Type	Wire Grid Parabola
Dimensions	890mm x 450mm
Weight	1.9 kg
Focal Length	320mm
Mounting Finish	Zinc Pre-Coat
Operating Temperature	-40°C to + 80°C
Accessory	Mounting Bracket



Typical value @ 25°C, unless otherwise specified.  
 Specifications are subject to change without prior notice.  
 ©2010 TRANSYSTEM INC. all rights reserved.

#### TranSystem. Inc.

Tel: + 886-3-578-0393 Fax: + 886-3-578-4111  
 Inquiries: sales@transystem.com.tw

Address: No. 1-2, Li-Hsin Rd I, Science-Based Industrial Park,  
 Hsinchu, Taiwan, R.O.C.  
 Web site: <http://www.transystem.com.tw>

